Changing your adjustable gullet bar

- 1 Using an allen key, unscrew the fitting which is located below the skirt near the head of the saddle, this will release the panel underneath.
- 2 Turn the saddle over and pull the panel away from the gullet bar and out of the point pocket, this will reveal the tree point fitting. Fold back the leather apron so you can see the full gullet bar.
- 3 Locate the fitting on the underside of the point and unscrew. This will release the gullet plate and then replace with your new width bar.
- 4 Replace the fittings through the tree point and into the gullet bar, tighten with the allen key.
- 5 Position the points back into the pockets and push in firmly.
- 6 Replace the large fittings positioned below the skirt, push them through and line up with the bushes in the panel. Tighten with your allen key.

You are now ready to go riding - enjoy!











Adjustable Gullet Sizing Guide



Cavaletti Collection Ltd | Unit 1 College Farm | Bosty Lane | Walsall | WS9 0LF t: 01922 263600 | e: contact@cavaletticollection.co.uk

www.cavaletticollection.co.uk



of

0

XW 105°

> W 95°

XXW 115°



M - 85° -

> NM 80°

Download onto a card based material and cut where shown for a guide to each width fit.

Alternatively take a template using a flexi curve and place onto fitting guide to match the suitable width.

Please note these are for guidance only we always recommend having your saddle fitted/checked by a professional saddle fitter.

Adjustable Gullet Sizing Guide

